## Investigation of Surface and Bulk Half-metallic Character of Fe<sub>3</sub>O<sub>4</sub> by Spin Resolved Photoemission

S. A. Morton (a), G. D. Waddill (a), S. Kim (b), Ivan K. Schuller (b), S. A. Chambers (c) and J. G. Tobin (d)

(a) Department of Physics, U. of Missouri-Rolla, Rolla, MO 65409, USA
(b) Department of Physics, U. of California San Diego, La Jolla, CA 92093, USA
(c) Pacific Northwest National Laboratory, Richland, WA 99392, USA
(d) Lawrence Livermore National Laboratory, Livermore, CA 94550 USA

The existence of a new class of magnetic materials displaying metallic character for one electron spin population and insulating character for the other was first postulated by DeGroot *et al* [1] in 1983 based on theoretical band structure calculations of the ferromagnetic Heusler alloy NiMnSb. Since then such half metallic materials, which by definition posses 100% electron polarization at the Fermi energy have attracted considerable theoretical, experimental, and technological interest as potential pure spin sources for use in spintronic devices [2], data storage applications, and magnetic sensors. In addition to Heusler alloys half metallic character has also been predicted to occur in a wide range of manganites [3], metallic oxides [4], and CMR systems [5]. However, such predictions have proven to be extremely difficult to confirm experimentally [6]. A major factor in this failure has proven to be significant experimental challenges in obtaining a clean stoichiometric surface with a magnetization that is truly representative of the bulk material and thus suitable for further study by magneto-optical or spectroscopic techniques.

In recent experiments at the ALS we have used spin resolved photoemission to study the role that surface reconstruction plays in the observed polarization of the half metallic candidate material magnetite,  $Fe_3O_4$ . Magnetite has a structure that is relatively simple in comparison to most other candidate half metals and it can be grown epitaxially using conventional deposition techniques [7], making it one of the strongest candidates for spintronic applications. However previous spin resolved measurements have shown that the polarization at the Fermi edge is only  $\sim 40\%$  [8] rather than the anticipated 100%.

By conducting spin resolved depth profile measurements and comparing the results to theoretical band structure calculations we have demonstrated that Fe<sub>3</sub>O<sub>4</sub> exhibits a semiconducting non-magnetic surface re-construction which significantly reduces the observed polarization but that, in contrast, the underlying bulk material is in fact very strongly polarized. Indeed, once the effects of this surface reconstruction are taken into account by theoretical models of the polarization an excellent match is obtained between the experimental spin resolved spectra and simulated spectra generated from theoretical spin polarized band structure calculations [9] (fig. 1). Hence our results strongly support the notion that Fe<sub>3</sub>O<sub>4</sub> is indeed a half-metallic material suitable for use in a new generation of spintronic devices.




Figure 1 Comparison of experimental spin resolved Fe<sub>3</sub>O<sub>4</sub> valence bands with equivalent simulated spectra derived from theoretical calculations that have been corrected to account for the presences of a nonmagnetic surface reconstruction

## References

- 1. R. A. de Groot et al., Phys. Rev. Lett. **50**, 2024 (1983).
- 2. S. A. Wolf, D. Treger, *IEEE Trans. Mag.* **36** 2748 (2000).
- 3. S. Jin et al., Science **264**, 413 (1994).
- 4. Z Zhang, S. Satpathy, *Phys. Rev. B* **44**, 13319 (1991).
- 5. W. E. Pickett, D. J. Singh, *Phys. Rev. B* **53**, 1146 (1996).
- 6. K. P. Kamper et al., Phys. Rev. Lett. **59** 2788 (1987).
- 7. S. A. Chambers, S. A. Joyce, *Surf. Sci.* **420**, 111 (1999).
- 8. S. F. Alvarado et al., Phys. Rev. Lett. **34**, 319 (1975).
- 9. S.A. Morton et al., Submitted to Surface Science Letters

This work was supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Materials Science Division, of the U.S. Department of Energy under Contract No. # R5-32633.A02. This work was performed under the auspices of the U.S Department of Energy by Lawrence Livermore National Laboratory under contract no. W-7405-Eng-48.

Principal Investigator: Ivan K. Schuller, Department of Physics, University of California San Diego, La Jolla, CA 92093. Phone: (858) 534-2540 fax: (858) 534-0173 Email: ischuller@ucsd.edu